



U-BEND LED GLASS TUBE SERIES

The LEDS U-Bend Glass Tubes are perfect for retrofit and lighting upgrade solutions.

FEATURES

- G13 Bi-Pin base
- UL Damp Listed
- Bright White 3500k CCT
- 45 year life or 50,000 hour of continuous use
- Maintenance Free - No Bulb Replacements
- 5 - Year Limited Warranty

SHIPPING INFORMATION

Order Code	UPC	Unit	Weight	Width	Length	Height
T8U1450	849489060156	Product	0.19 kg 0.42 lbs	4.1 cm 1.61"	57 cm 22.44"	2.48 cm 0.98"
T8U1450	50849489060151	Carton	3.78 kg 8.34 lbs	16.5 cm 6.50"	60 cm 23.62"	21.5 cm 8.46"
T8U1460	849489060163	Product	0.19 kg 0.42 lbs	15.2 cm 5.98"	57 cm 22.44"	2.48cm 0.98"
T8U1460	50849489060168	Carton	5.97 kg 12.77 lbs	38.5 cm 15.16"	60 cm 23.62"	21.5 cm 8.46"

G13 NON-SHUNTED SINGLE-END POWER

Order Code	Part Number	Watts	Lumens ¹	CCT ²	Avg Life ³	CRI ⁴	Voltage	Operating Temp	Power Factor	Operating Frequency
T8U1450	T8-U1.67-1335-B	13	1900	3500	50000	80	120-277	Min. -4°F (20°C)/Max. 115°F (45°C)	>0.9	50/60
T8U1460	T8-U6-1335-B	13	1900	3500	50000	80	120-277	Min. -4°F (20°C)/Max. 115°F (45°C)	>0.9	50/60

This device complies with Part 15 of the FCC Rules. Operation is subject to the following conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us/fcc15b

1. Thermally stable typical lumens (+/- 10%)

2. Thermally stable CCT (+/- 10%)

3. Average life based on 70% lumen maintenance

4. Color rendering index/Ra