





LEDS T8 TUBE SERIES

The LEDS T8 Tubes are perfect for new construction, retrofit and lighting upgrade solutions. High output and top of the line specifications. Available in multiple wattage and lumen output configurations to meet any lighting application.

FEATURES

- · High efficacy, long life LEDs
- High efficiency driver: 120V 277V
- · Glass construction for superior thermal management.
- 320° beam angle
- 5-Year warranty
- Maximum 24 hours for full recharge time














Nominal	A	B	C
Length	(Illuminated Length)	(Body Length)	(Diameter)
48"	44.70"	47.15"	

T8 SINGLE END POWER



Use G13 Non-Shunted Sockets Wired to Line Voltage.

Order Code	Part Number	Watts	Lumens	сст	CRI	Voltage			
T81111	T8-F4-1040-B	10	1800	4000	>80	120-277			
T81112	T8-F4-1050-B	10	1800	5000	>80	120-277			
T81118	T8-F4-840-B	8.5	1700	4000	>80	120-277			
T81119	T8-F4-850-B	8.5	1700	5000	>80	120-277			
T81116	T8-F4-2540-B	25	3800	4000	>80	120-277			
T81117	T8-F4-2550-B	25	3800	5000	>80	120-277			
- DIMMABLE -									
T81125	T8-F4-1240-B-D	12	1800	4000	>80	120-277			

APPLICATION NOTES

- 1. Operating Temperature Range Between -20°C and +45°C (-4°F and +113°F)
- 2. Ballast Bypass Required.

Use G13 Non-Shunted Sockets Wired to Line Voltage.

WARRANTY: This product has a warranty for a period of 5 years from the date of purchase. The warranty is invalid in the case of improper installation, tampering, or removal of the Q.C. date label. Installation in an improper working environment or installation not according to the current edition of the National Electric Code also invalidates the warranty. Should this product fail during the warranty period, it will be replaced free of charge, subject to correct installation and return of the faulty unit. LEDS, LLC does not accept responsibility for any installation costs associated with the replacement of this product. This warranty is in addition to the statutory rights in the country of purchase. LEDS, LLC reserves the right to alter specifications without prior notice.

