

DATE:	PROJECT:
TYPE:	NOTES:
PART #:	

## LED CANOPY LIGHT

5000K | 120-277V

### KEY FEATURES

LEDS Canopy Fixtures deliver high-quality, energy-efficient lighting, ideal for parking garages, carports, and underpasses. Designed for versatility, they are available in various wattage and lumen output configurations to suit diverse applications. Featuring fins and advanced grooves for superior heat dissipation, professional light distribution, and high-performance reflectors, these fixtures ensure exceptional performance. With an operating temperature range of -22°F to 122°F, UL Wet Location listing, and a 5-year warranty, they provide reliable and durable lighting solutions.

### CCT & Light Quality

- 5000K, >80+ CRI

### Light Output

- Light Output: 4800-8400lm
- Efficacy Rating: 120 LPW
- Life time rating 50,000 hrs.

### SPECIFICATIONS

#### Construction

- Fins and advanced grooves for superior heat dissipation
- Professional light distribution and high-performance reflectors

#### Electrical

- High efficiency LED Driver at >90%
- 120-277V, 50/60hz
- Operating Temperature: -22°F to 122°F (-30°C to 50°C)

#### Warranty

5-Year Standard Warranty. See terms at: [LEDS-LLC.com](http://LEDS-LLC.com)

KEY DATA	
Lumen	20100lm - 20250lm
Wattage	150W
Efficacy Range (LPW)	>135
Reported Life (Hours)	L70 / 50,000



#### Certifications & Test Data

- cULus Certified, Wet Location, IP65
- RoHS compliant with no lead or mercury
- DLC Standard Listed. Search [qpl.designlights.org](http://qpl.designlights.org) for details



### STOCK ORDERING INFORMATION

Part Number	Order Code	Size	Lumen Package	Wattage	Efficacy	CCT	CRI	Voltage	DLC Listed*
CP-8.5-4050-MV	CP4050	8.5 in	4800lm	40W	120 LPW	5000K	>80 (min)	120-277V	Standard
CP-10-7050-MV	CP7050	10 in	8400lm	70W	120 LPW	5000K	>80 (min)	120-277V	Standard

### DIMENSIONS

