

DATE:	PROJECT:
TYPE:	NOTES:
CATALOG #:	

## OUTDOOR EMERGENCY WALL PACK

### KEY FEATURES

Introducing the outdoor emergency wall pack: a durable lighting solution with a die-cast aluminum housing, polycarbonate lens, mirror reflector, and photocell with self-diagnostics. It is IP65 protected, suitable for wet locations, and compliant with UL 924 and CEC Title 20 standards, making it an excellent choice for outdoor emergency lighting.

- Photocell and self-diagnostic
- 12W 1100lm for AC mode | 5W 430lm for emergency mode
- Suitable for Wet Locations
- IP65 protection
- UL 924 and CEC Title 20 Compliant

### SPECIFICATIONS

#### Construction

- Die-cast aluminum housing
- UL 94V-0 flame retardant, fire-resistant

#### Electrical

- Maintenance-free 4.8V NiCad battery
- Maximum 24 hr for full charge
- Discharge time: 90 minutes
- Input Rating: 3.0W, 70mA
- Input Voltage: 120-277VAC 60Hz
- Operating Temperature: 32°F (0°C) to 104°F (40°C)

#### Warranty

5-Year Standard Warranty. See terms at: [LEDS-LLC.com](http://LEDS-LLC.com)



#### Certifications & Test Data

- Wet Location
- UL 924 Standard for Emergency Lighting and Power Equipment
- Meets NFPA 101 Life Safety Code, NEC, OSHA California Energy Commission (CEC) Title 20 Compliant
- RoHS compliant with no lead or mercury



## STOCK ORDERING INFORMATION

Part Number	Description	AC Mode		Emergency Mode		Input Voltage	Battery	Charging Time	Emergency Run Time
		Watts	Lumens	Watts	Lumens				
EMWP-12-50-MV	Bronze LED Emergency Wall Pack	12W	1100lm	5W	430lm	120-277V	4.8V NiCad battery	24 hrs	90 mins

#### Dimensions

10.4 \* 6.4 \* 3.86 in  
(265 \* 160 \* 98mm)

