

|         |          |
|---------|----------|
| DATE:   | PROJECT: |
| TYPE:   | NOTES:   |
| PART #: |          |

## FLOOD LIGHT

5000K | 4500LM

### KEY FEATURES

LEDS Flood Lights deliver exceptional performance for new construction, retrofits, and lighting upgrades. Featuring Lumileds LEDs for high efficacy and long life, a high-efficiency driver (120V-277V), and robust die-cast aluminum construction for superior thermal management. With an 80° beam angle and premium optics, these flood lights ensure even light distribution and optimal control. Rated for up to 50,000 hours (L70) and backed by a 5-year warranty, they offer a reliable and energy-efficient lighting solution.

### CCT & Light Quality

- 5000K, >80+ CRI

### Light Output

- Light Output: 4500lm
- Efficacy Rating: 100 LPW
- Life time rating 50,000 hrs.

### SPECIFICATIONS

#### Construction

- Die-cast aluminum construction for superior thermal management
- Beam Angle 80°

#### Electrical

- Premium optics for even light distribution, utilization and control
- 120-277V, 50/60hz
- Operating Temperature: -22°F to 122°F (-30°C to 50°C)

#### Warranty

5-Year Standard Warranty. See terms at: [LEDS-LLC.com](http://LEDS-LLC.com)

| KEY DATA              |              |
|-----------------------|--------------|
| Lumen                 | 4500lm       |
| Wattage               | 45W          |
| Efficacy Range (LPW)  | 120          |
| Reported Life (Hours) | L70 / 50,000 |



### Certifications & Test Data

- cULus Certified, Wet Location
- RoHS compliant with no lead or mercury
- DLC Standard Listed. Search [qpl.designlights.org](http://qpl.designlights.org) for details



### STOCK ORDERING INFORMATION

| Part Number | Order Code | Lumen Package | Wattage | Efficacy | CCT   | CRI       | Voltage  | DLC Listed* |
|-------------|------------|---------------|---------|----------|-------|-----------|----------|-------------|
| FL-4550-MV  | FL1111     | 4500lm        | 45W     | 120 LPW  | 5000K | >80 (min) | 120-277V | Standard    |

### DIMENSIONS

