

DATE:	PROJECT:
TYPE:	NOTES:
PART #:	

## LINE VOLTAGE GIMBAL TRACK HEAD FOR PAR38 LIGHT SOURCE

### KEY FEATURES

Line voltage die-cast aluminum gimbal fixtures designed for PAR38 light source (purchased separately). The yoke allows full adjustment of the light source position for precise aiming, and two tightening knobs ensure the angle stays securely locked.

- Die-cast aluminum provides superior strength and rigidity
- Low profile, aesthetic design
- Adjustable yoke for custom aiming
- One or two circuit track capable

### Housing

- Iron / die-cast aluminum construction
- Gimbal appearance and design features
- All edges are softened for aesthetic appearance

### Yoke

- Iron yoke connects fixture housing to electrical contact head.
- Dual plastic angle tightening knobs maintain clean, decorative appearance of the fixture and provides secure angle position

### Wiring

- Teflon coated wire lead connects socket and housing to electrical contact head
- Teflon coating is durable and resists heat degradation from lamp and housing radiation

### Finishes

- Black, White and Satin Nickel heat rated baked enamel paint
- Custom painting or anodizing for special applications is also available
- Custom finishes will require lead times that vary depending on vendor schedule. Please consult factory for quotation

### Warranty

5-Year Standard Warranty. See terms at: [LEDS-LLC.com](http://LEDS-LLC.com)



### Certifications & Test Data

- cULus Listed
- RoHS compliant with no lead or mercury
- Rated for FCC part 15 Class B for use in residential or commercial applications



## STOCK ORDERING INFORMATION

Part Number	Description	Lamp
K2053	Gimbal Track Head Only	Fits PAR38 E26 24W MAX ( <b>ordered separately</b> )

**ACCESSORIES**



**K500**  
Global Adaptor  
Finish: WH/BK



**K600**  
Single/Two Circuit Live End  
Finish: WH/BK



**K601**  
Single /Two Circuit End Feed  
Finish: WH/BK



**K602**  
Single/Two Circuit  
Flexible Connector  
Finish: WH/BK



**K604**  
T-bar Attachment Clips  
For T-bar Drop Ceiling  
Finish: WH/BK/SN



**K605**  
Single/Two Circuit  
Floating Canopy  
Finish: WH/BK



**K606**  
Single/Two Circuit Live  
End With Box Cover  
Finish: WH/BK



**K602**  
Single/Two Circuit  
Flexible Connector  
Finish: WH/BK



**K608**  
Mini Coupling  
Finish: WH/BK



**K609**  
Single/Two Circuit  
T-Connector  
Finish: WH/BK



**K610**  
Single Circuit 90° Connector  
Finish: WH/BK



**K611**  
Single/Two Circuit  
X-Connector  
Finish: WH/BK



**K612**  
Live End With Cord & Plug  
Finish: WH/BK  
Available in 2-wire, 3-wire, 4-wire



**K5-3**  
Single Circuit/Two Circuit Track  
Single Circuit Track is rated for 2400W  
Features 12-gauge copper conductors and a separate ground  
conductor. Two circuit track includes 12-gauge copper  
conductors and features a double load capacity at 4800W  
max.  
Single/Two Circuit Track is available in white, black and satin  
nickel finishes, and in 4, 6, and 8-foot sizes, and can also be  
field cut to your preference.