

2.5" LED PUCK LIGHT 3500K | 120V

KEY FEATURES

CCT & Light Quality

- 3500K
- >80+ CRI
- 120V, 60Hz
- Lasts 45 years* or 50,000 Hours Continuous Use
- Energy Saving 5 Watt Integrated LED

Installation

- Two low-profile spring retention clips for a secure fit—no need for a separate recessed housing or junction box
- · 6 foot wire leads can be adjusted to customers specific specification
- Cut out size 2 3/4"

Construction

- Stamped aluminum heat sink and injection mold PC lens
- Each puck has a 6ft cable

Warranty

5-Year Standard Warranty. See terms at: LEDS-LLC.com

KEY DATA			
Lumen	460LM		
Wattage	5W		
Efficacy Range (LPW)	92 LPW		
Reported Life (Hours)	Minimum 50,000 hrs		

STOCK ORDERING INFORMATION

DATE:	PROJECT:
TYPE:	NOTES:
PART #:	







Certifications & Test Data

- Built to UL standards
- RoHS compliant with no lead or mercury



Part Number	Order Number	Size	Lumen Package	Wattage	ССТ	CRI	Efficiency	Voltage	Beam Angle
WDOL0003	53825131	2.5"	460LM (each 2.5" down light)	5W	3500K	>80 (min)	92 LPW	120V	100°

SHIPPING INFORMATION

Order Number	UPC	Product Dimensions	Master Carton Bar Code	Master Carton Dimensions	Master Carton Weight
53825131	849489063270	3in x 0.87in. (7.72 x 2.2cm)	50849489063275	24.57in x18.19in x4.17in (62.4 x 46.2 x10.6cm)	11.26lbs

ACCESSORIES (sold separately)

Extension Cable



Order number

End Connectors: One Male One Female Isolated Driver (one driver for six packs max)





Order number 90600733

A.	

Operating Frequency	Channel
60Hz	6-channel
	· · · · · · · · · · · · · · · · · · ·

LEDS:

All specifications are subject to change without notice. All reported values are typical, measured under laboratory conditions @ 25° C (77° F). Actual performance can vary slightly as a result of end-user application & environment.