

DATE:	PROJECT:
TYPE:	NOTES:
CATALOG #:	

## T8 LED U-BEND TUBES TYPE C

### KEY FEATURES

The U-Bend T8 Tubes with 2 G13 Medium Bi-Pin base offer a convenient plug-and-play replacement for fluorescent tubes. Featuring a superior diffusion coating for durable, uniform light with no yellowing, these tubes are c-UL-us classified and recognized, making them an excellent choice for indoor residential and commercial applications.

#### CCT & Light Quality

- 3500K, 80+ CRI

#### Light Output

- Light Output: 1900lm
- Efficacy Rating: up to 146 LPW
- Life time rating 50,000 hrs.

### SPECIFICATIONS

#### Construction

- Glass construction for superior thermal management.
- High efficacy, long life LEDs
- 2 G13 Medium Bi-Pin Base
- Suitable for damp locations and open fixtures

#### Electrical

- Operates at 120-277, 50/60Hz
- Power Factor: > 0.9 nominal | THD <20%
- Operating Temperature: -4°F to 113°F (-20°C to 45°C)

#### Warranty

5-Year Standard Warranty. See terms at: [LEDS-LLC.com](http://LEDS-LLC.com)



#### Certifications & Test Data

- cULus Classified
- RoHS compliant with no lead or mercury
- DLC Standard Listed. Search [qpl.designlights.org](http://qpl.designlights.org) for details



### STOCK ORDERING INFORMATION

Part Number	Order Code	Lamp	Lumen Package	Wattage	Efficacy	CCT	CRI	Voltage	DLC Listed*
T8-U1.67-1335-C	T8U1450D	Type C	1900lm	13W	146 LPW	3500K	80 (min)	120-277V	Standard
T8-U6-1335-C	T8U1460D	Type C	1900lm	13W	146 LPW	3500K	80 (min)	120-277V	Standard

### DIMENSIONS

Order Code	A	B	C	D	E
T8U1460D	5.98 in	22.5 in	1.14 in	1.03 in	1.09 in
T8U1450D	1.61 in	22.5 in	1.14 in	1.03 in	1.09 in



### REMOTE DRIVER

Order Code	Description
T8UD14	Remote Driver for Type C U Bend Lamps 1 for 4 lamps
T8UD12	Remote Driver for Type C U Bend Lamps 1 for 2 lamps

