

FLAT PANELS

CCT & LUMEN SELECTABLE | 120-277V

KEY FEATURES

These DLC Premium-rated flat panel lights are available in three sizes: 1'x4', 2'x4', and 2'x2'. Each panel offers customizable lighting with three selectable lumen/wattage outputs, allowing you to tailor the brightness to your specific needs. In addition, the panels feature three selectable color temperatures, ensuring flexibility for various environments, from office spaces to commercial applications. With energy efficiency and superior performance, these flat panels deliver reliable, high-quality lighting solutions.

CCT & Light Quality

· 3500K | 4000K | 5000K, >80+ CRI

Light Output

- · Light Output: 3750lm 5200lm
- Efficacy Rating: >125 LPW
- \cdot Life time rating 50,000 hrs.

Dimming

· 0-10V dimming standard

SPECIFICATIONS

Construction

- · White Polycarbonate Diffused Lens
- · Lightweight Aluminum Frame
- · Integrated Steel Driver Channel

Optics

• PF 0.9

Electrical

- · THD < 20%
- · 120-277V, 50/60 Hz

Warranty

5-Year Standard Warranty. See terms at: <u>LEDS-LLC.com</u>

DATE: PROJECT: TYPE: NOTES: CATALOG #:



Certifications & Test Data

- · cULus Classified, Damp Location
- · RoHS compliant with no lead or mercury
- · DLC Premium Listed. Search qpl.designlights.org for details









STOCK ORDERING INFORMATION

Catalog Part Number	Order Code	Size	Lumen Package	Wattage (Selectable)	Efficacy	CCT (Selectable)	CRI	Voltage	Dimming	DLC Listed®
FP-24-LA3-CCT3-MV-D	FP2400	2'x4'	5000lm at 35K/50K at 40W 5200lm at 40K at 40W	30/35/40W	125 LPW	35/40/50K	80	120-277V	0-10V	Premium
FP-22-LA3-CCT3-MV-D	FP2200	2'x2'	3750lm at 35K/50K at 30W 3900lm at 40K at 30W	20/25/30W	125 LPW	35/40/50K	80	120-277V	0-10V	Premium
FP-14-LA3-CCT3-MV-D	FP1400	1'x4'	3750lm at 35K/50K at 30W 3900lm at 40K at 30W	20/25/30W	125 LPW	35/40/50K	80	120-277V	0-10V	Premium







