

DATE:	PROJECT:
TYPE:	NOTES:
PART #:	

12IN & 15IN SLIM LED FLUSH MOUNTS WITH SELECTABLE CCT AND WATTS

KEY FEATURES

CCT & Light Quality

- 5 Selectable CCTs (2700K, 3000K, 3500K, 4000K, 5000K)
- >90+ CRI

Light Output

- 3 Selectable Wattage/Lumen Levels:
12" : 1600LM-1760LM-1920LM (20W- 22W-24W)
15" : 1920LM-2240LM-2560LM (24W- 28W-32W)
- Life time rating 50,000 hrs.

Dimming, Controls

- Triac dimming
- Quick-Access Selectable Controls

SPECIFICATIONS

Construction

- Ultra Slim Design - 0.6" profile blends seamlessly into ceilings
- Easy Twist & Lock Installation
- Frosted lens

Electrical

- 120V, 60Hz
- Operating temperature: -20° C (-4° F) / 45° C (113° F)

Warranty

5-Year Standard Warranty. See terms at: LEDs-LLC.com



15"



12"



Certifications & Test Data

- Built to ETL standards
- Damp Location
- RoHS compliant with no lead or mercury
- Driver rated for FCC part 15 Class B for use in residential or commercial applications



STOCK ORDERING INFORMATION

Order Code	Part Number	Size	Lumen Package	Wattage	CCT	CRI	Voltage	Dimming
FM1100	SFM-12-LA3-5CCT-SV-D	12"	1600LM-1760LM-1920LM	20W- 22W-24W	2700K, 3000K, 3500K, 4000K, 5000K	>90	120V	TRIAC
FM1200	SFM-15-LA3-5CCT-SV-D	15"	1920LM-2240LM-2560LM	24W- 28W-32W	2700K, 3000K, 3500K, 4000K, 5000K	>90	120V	TRIAC

DIMENSIONS

Order Code	Size	Dimensions
FM1100	12"	11.81" Dia x 0.67"
FM1200	15"	14.96" Dia x 0.67"



Quick-Access Selectable Controls – Quickly adjust wattage and color temperature with built-in switches, conveniently located for fast and flexible customization.

Easy Twist & Lock Installation – Securely mount the bracket to the junction box, then simply twist the fixture into place for a quick and hassle-free setup.